

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention relates generally to computer systems and specifically to co-located computer systems in a framework including removable function modules which add modular functionality.

### 2. Description of the Related Art

Many commercial businesses and enterprises make extensive use of personal computers (PCs) in their daily operations. Typically, each user of a personal computer in the enterprise has a networked PC at their desk or work area. As the number of networked computer systems utilized in an enterprise increases, the management of such resources becomes increasingly complex and expensive. Some of the manageability issues involved in maintaining a large number of networked computer systems include ease of installation and deployment, the topology and physical logistics of the network, asset management, scalability (the cost and effort involved in increasing the number of units), troubleshooting network or unit problems, support costs, software tracking and management, as well as the simple issue of physical space, be it floor space or room on the desktop. In addition, there are security issues regarding physical assets, data protection, and software control. In many business establishments, such as call centers, there is no need for the user to install software on his/her unit, and in fact, management may specifically forbid employees from doing so. However, the standard personal computer configuration inherently provides the user this ability because the system is typically located with the user, and includes a floppy drive, CDROM, and one or more hard drives. Ensuring that unauthorized software is not installed on any of the machines in the network involves periodically personally auditing the software contents of each machine, at substantial cost in time and effort.

Many of these issues may be addressed by centralizing the locations of the personal computers, such as by installing multiple PCs into a central frame or cabinet.

Prior art has generally been applied to servers and has focused on installing a standard PC into a sliding cabinet, where the term "standard PC" refers to a motherboard with extension slots, floppy disc and CD drives, and a general open architecture supporting almost any standard expansion card.

5           Two variations of this approach are typical. The first is to stand a standard PC motherboard on its edge to create a taller, thinner PC. All connections are on a rear panel and any ancillary boards plug in sideways to the motherboard. The second variation consists of plugging the PC motherboard into a back plane (either vertical or horizontal) which also receives any ancillary cards required. Both of these configurations lend  
10 themselves to a slide-drawer approach to packaging. However, there are numerous disadvantages with these approaches due to the fact that various compromises in size and feature set have been made to accommodate a wide assortment of feature addition cards. Such disadvantages include a higher product cost and a large physical size for each unit. In addition, the terminations and connections at the back of each unit are awkward to use  
15 – in the case of the first approach the terminations are on the motherboard, requiring the removal of all connectors before removing the board from its slide drawer case; in the case of the back plane based system the edge connections for each card have a high number of connections which creates a connection environment which is both fragile and difficult to administer.

20           One issue with clustered or co-located computers is adding functionality to each of the computers. In the present disclosure, the term "feature device" refers to a device that may be added to a computer which adds functionality to the computer. The prior art approach for adding operational features to clustered personal computers has typically been to install each feature device in a central location and run cables from each feature  
25 device to the appropriate I/O ports on each computer. This approach has numerous disadvantages, described below.

Using a variety of individual feature devices means the replication of items such as the feature device chassis and power supplies. These items are common to all the elements of the system but in a practical situation must reproduced individually in each

feature device that provides a function or service. This replication substantially increases the cost of the system.

Typically additional feature devices in computers are designed and built by different manufactures, as each manufacturer tends to specialize in a given feature set.

5 Connecting these divergent devices together requires both the fabrication and installation of many connecting cables, thereby greatly increasing the complexity and difficulty of system installation.

Additionally, scaling a particular feature upward, i.e., applying the new feature to added computer units compounds the issues of wiring and physical placement noted  
10 above. Such approaches resist expansion or extension of the system by creating a disproportionately heavy installation workload, and so decreases the scalability of the system.

Typically the multiple electronic packages used to add features to a system require additional space, cooling, and attention. The addition of the feature devices to a system  
15 may require redistribution of the original installed hardware, which may result in considerable planning effort and physical labor, as well as affecting the size of the system, which then may affect the space requirements and consequently, the location of the system.

Combining multiple feature sets in a system requires careful consideration of  
20 possible unintended and undesirable consequences caused by the relationships among processes and equipment. Considerable research and consideration should be given to the synergy of the feature elements in a system, which may be time consuming and expensive, and which may substantially increase the difficulty of designing the system. Once installed, tuning the actual performing relationships between the various hardware  
25 based feature sets requires substantial debugging time, cost, and special talent. The long term performance of the system is a function of interfacing as well as unique signaling conditions, and the increased cabling requirements may cause substantial performance limitations.

Finally, the use of multiple and varied feature devices from different vendors, which are typically connected in series, lowers the reliability of the system by compounding the devices' Mean Time Between Failures, thus decreasing the reliability of the system.

- 5           Therefore, improved systems and methods are desired for adding modular functionality to co-located computer systems.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220

## SUMMARY OF THE INVENTION

The present invention comprises various embodiments of a system comprising one or more centrally located computers, wherein removable function modules may be used to provide additional functionality to the computers.

In one embodiment the system may include a cabinet or chassis, referred to as a cage, which has a plurality of slots. The computers may comprise computer cards which may be adapted to be inserted into respective slots of the cage. The cage may include a cage connector which is adapted to couple to an edge connector on each inserted computer card. Each computer card may be operable to slide into a slot the computer cage, thereby engaging the computer card edge connector with the cage connector. A removable function module may be operable to engage the cage connector, e.g., the removable function module may include a module connector that connects to the cage connector. The use of the cage connector as an intermediate connection between the computer cards and the function module allows the removal and/or exchange of computer cards without the need to disconnect the cables from the cage, as well as the removal and/or exchange of the function module without the need to disconnect the computer cards.

In one embodiment, the function module may include interfacing cable connectors corresponding to each computer card slot in the cage. The cable connectors may be operable to couple to one or more cables for communicating with external systems, such as networks and/or human interface devices. In one embodiment, the external connectors used for the cable connectors may be standard connectors, including one or more of RJ45, db9, db25, or dbhd15 connectors, or any other type of standard connector.

The function module may include one or more network cable ports for receiving one or more network cables to interface with one or more networks, as well as one or more human interface cable ports for receiving one or more human interface cables to interface with one or more human interfaces. In one embodiment, the cable ports may

comprise RJ-45 connectors. In addition, the function module may also include a power supply which may be operable to supply power to the function module components.

In one embodiment, a function module may include circuitry which provides additional functionality to the computer cards. The function module may include multiple circuit boards to provide multiple additional functions to the computer system. In one embodiment, the function module may include a top cover and a bottom cover which may encapsulate multiple circuit boards, such as a network board and a layer 3 switch and router (SW3) board. In one embodiment, the network board may comprise an Ethernet board with active Ethernet Switch types 1 and 2. In one embodiment, the SW3 board may comprise an Ethernet Level 3 Switch and Router board. In one embodiment, the Ethernet board may connect to the cage connector, while the SW3 board is "piggybacked" on the Ethernet board. The Ethernet board may be operable to pass certain signals upward to the piggybacked SW3 board, thus permitting additional signal processing to occur.

In various embodiments, the function module may provide or include one or more of the following functions:

- at least one cable connection module which is operable to provide cable connections to one or more cables for the plurality of computer cards;

- at least one network card which is operable to provide a network interface to the plurality of computer cards;

- at least one network switch which is operable to perform network switching functions for the plurality of computer cards;

- at least one data switch which is operable to perform data switching functions for the plurality of computer cards; at least one router which is operable to perform network routing functions for the plurality of computer cards;

- at least one network processing unit which is operable to perform network processing functions for the plurality of computer cards;

a Gigabit Ethernet network interface which includes a Gigabit Ethernet bus, wherein the Gigabit Ethernet network interface comprises a plurality of Gigabit Ethernet ports for each of at least a subset of the plurality of computer cards;

5 at least one gateway which is operable to perform gateway functions for the plurality of computer cards;

at least one firewall which is operable to restrict network access to the plurality of computer cards;

10 a human interface switching unit, wherein the human interface switching unit is configurable to route encoded human interface signals from one or more of the plurality of computer cards to one or more of a plurality of remote human interface devices coupled to the removable function module;

at least one analog POTS unit which is operable to provide standard analog telephony services to the plurality of computer cards;

15 at least one digital telephone which is operable to provide digital telephony services to the plurality of computer cards;

at least one PBX units which is operable to provide PBX services to the plurality of computer cards;

at least one Voice over Internet Protocol (VoIP) telecommunication device which is operable to provide VoIP services to the plurality of computer cards; and/or

20 at least one MPEG video unit which is operable to provide MPEG video services to the plurality of computer cards.

In one embodiment, a plurality of computer cards may be inserted into the cage, each making electrical contact with the cage connector. A first removable function  
25 module may be attached to the cage, thereby coupling to at least a subset of the inserted computer cards via the module connector which connects to the cage connector. Attaching the first removable function module to the cage may include attaching one or more cables to the cable connectors to interface with external systems. For example, one or more network cables may be connected to network cable ports for interfacing to one or

more networks, and/or one or more human interface cables may be connected to human interface ports for interfacing to one or more human interfaces. In one embodiment, one or more cables may be connected to the function module to couple the inserted computer cards to a telephone line. The first removable function module may be operable to  
5 provide a first functionality to the inserted computer cards, and may include any of the function modules described above. Then, the first removable function module may be removed from the cage assembly which may include removing some or all of the one or more attached cables. Finally, a second removable function module may be attached to the cage, in the manner described above. The second removable function module may be  
10 operable to provide a second functionality to the inserted computer cards, and may include any of the function modules described above.

The components of each human interface may include a keyboard, a pointing device such as a mouse, a display device such as a computer monitor, and/or any other human interface components. Each computer may communicate with the human  
15 interface by sending and receiving encoded human interface signals transmitted over one or more connecting cables. Each computer may include all the elements that make up a standard personal computer, such as a PC motherboard with a microprocessor CPU, memory, and network and interface logic, configured on a single card, and may be referred to as a computer card. In one embodiment, the network logic may include a LAN  
20 interface, Ethernet, or other network interface. In one embodiment, the interface logic may include keyboard, mouse, video, audio, USB, and/or any other interface circuitry associated with a PC motherboard, as well as human interface logic. The computer card may also include one or more hard disk drives or optical drives and a power supply which may be operable to convert the local main power to the appropriate voltages for the  
25 computer. The computer card may also include an interfacing edge connector, which may be operable to transmit video, mouse, keyboard, USB, and Ethernet signals, as well as any other peripheral or network signals to the user interface or a network, respectively.



Thus, in various embodiments, a variety of removable function cards may be added and/or removed from the cage assembly to provide various sets of functionality to the inserted computer cards as needed. The fact that both the computer cards and the function modules may be removed from the cage assembly without removing the other greatly simplifies the process of configuring and reconfiguring the system. The inclusion of removable function modules in the system provides a simple and affordable mechanism whereby additional feature sets may be provided for the plurality of computing systems as required. The use of function modules as described above enables an administrator to apply standard feature sets to multiple computing systems with ease and greatly decreases cabling requirements for the system.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

Other advantages and details of the invention will become apparent upon reading the following detailed description and upon reference to the accompanying drawings in which:

Figure 1 is a block diagram of a computing system comprising a host computer coupled to a remote user interface, according to one embodiment;

Figure 2 illustrates a computer card mounted on a slide drawer, according to one embodiment;

Figure 3 is a detailed diagram of the computer card of Figure 2;

Figure 4 illustrates a system comprising a plurality of computer cards coupled to a plurality of corresponding user interfaces; and

Figure 5 is a block diagram of the system of Figure 4;

Figure 6 illustrates the computer system of Figures 4 and 5, with a removable function module, according to one embodiment;

Figure 7 illustrates one embodiment of a removable function module;

Figure 8 illustrates one embodiment of a multi-board function module; and

Figure 9 is a flowchart of a method for configuring a plurality of computing systems.

While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that the drawings and detailed description thereto are not intended to limit the invention to the particular form disclosed, but on the contrary, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the present invention as defined by the appended claims.

## **DETAILED DESCRIPTION OF THE EMBODIMENTS**

### **Incorporation by Reference**

U.S. Provisional Patent 60/144,809 titled "A Technique To Extend The Operating  
5 Distance Of A Universal Serial Bus" is hereby incorporated by reference in its entirety as  
though fully and completely set forth herein.

U.S. Patent No. 6,119,146 titled "Computer Network Having Multiple Remotely  
Located Human Interfaces Sharing A Common Computing System", which was filed  
May 4, 1998, whose inventors are Barry Thornton, Andrew Heller, Daniel Barrett, and  
10 Charles Ely, is hereby incorporated by reference in its entirety as though fully and  
completely set forth herein.

U.S. Patent No. 6,038,616 titled "Computer System With Remotely Located  
Interface Where Signals Are Encoded At The Computer System, Transferred Through A  
4-Wire Cable, And Decoded At The Interface", which was filed May 4, 1998, whose  
15 inventors are Barry Thornton, Andrew Heller, Daniel Barrett, and Charles Ely, is hereby  
incorporated by reference in its entirety as though fully and completely set forth herein.

U.S. Patent No. 6,037,884 titled "Technique To Encode Multiple Digital Data  
Streams In Limited Bandwidth For Transmission In A Single Medium", which was filed  
October 27, 1997, whose inventor is Barry Thornton, is hereby incorporated by reference  
20 in its entirety as though fully and completely set forth herein.

U.S. Patent No. 6,020,839 titled "Analog Technique To Detect Asymmetric Radio  
Frequency Pulses", which was filed October 27, 1997, whose inventor is Barry Thornton,  
is hereby incorporated by reference in its entirety as though fully and completely set forth  
herein.

25 U.S. Patent No. 6,012,101 titled "Computer Network Having Commonly Located  
Computing Systems", which was filed May 4, 1998, whose inventors are Andrew Heller,  
Barry Thornton, Daniel Barrett, and Charles Ely, is hereby incorporated by reference in its  
entirety as though fully and completely set forth herein.

U.S. Patent No. 5,994,952 titled "Narrow Band-Pass Interferometric Filter Having Enhanced Operational Characteristics", which was filed October 22, 1997, whose inventor is Barry Thornton, is hereby incorporated by reference in its entirety as though fully and completely set forth herein.

5 U.S. Patent No. 5,966,056 titled "Method And Apparatus For Enabling The Transmission Of Multiple Wide Bandwidth Electrical Signals", which was filed July 3, 1996, whose inventor is Barry Thornton, is hereby incorporated by reference in its entirety as though fully and completely set forth herein.

10 U.S. Patent No. 5,926,172, titled "Video Data Transmission And Display System And Associated Methods For Encoding/Decoding Synchronization Information And Video Data", which was filed September 23, 1997, whose inventor is Williams Hanley, is hereby incorporated by reference in its entirety as though fully and completely set forth herein.

15 U.S. Patent Application Ser. No. 09/179,809 titled "A Technique To Transfer Multiple Data Streams Over A Wire Or Wireless Medium" is hereby incorporated by reference in its entirety as though fully and completely set forth herein.

20 U.S. Patent Application Ser. No. 09/619,989 titled "System And Method For Providing A Remote Universal Serial Bus", which was filed July 20, 2000, whose inventors are Dan Barrett, Mike Barron, and Andrew Heller, is hereby incorporated by reference in its entirety as though fully and completely set forth herein.

U.S. Patent Application Ser. No. 09/680,760 titled "System And Method For Combining Computer Video And Remote Universal Serial Bus In An Extended Cable", which was filed October 6, 2000, whose inventor is Barry Thornton, is hereby incorporated by reference in its entirety as though fully and completely set forth herein.

25

Figure 1: A Computer System Coupled To A User Interface

Figure 1 is a block diagram of a computing system comprising a computer 108 and a human interface (HI) 113. The HI may optionally be located remotely from the computer 108. Alternately, the HI 113 may instead be located closely to the computer

system. The following describes one embodiment of the invention, where the HI 113 may be located remotely from the computer 108, however this is not intended to limit the invention. One or more connecting cables 105 may connect the computer 108 to the HI 113. As Figure 1 shows, in one embodiment, the components of the HI may include a keyboard 110, a pointing device such as a mouse 111, a display device 112 such as a computer monitor, and/or any other human interface components. The computer 108 may communicate with the human interface 113 by sending and/or receiving encoded human interface signals 107 transmitted over the one or more connecting cables 105. The separation of the human interface 113 from the computer 108 may provide a number of benefits to a business or enterprise, including the isolation of means to install software, such as CDROMs, from the user, as well as the central location of multiple computers which may simplify both hardware and software maintenance. Additionally, the central location of multiple computers may accommodate the use of various feature devices or function modules, described below with reference to Figures 6-9. Further benefits of the system of Figure 1 are described in U.S. Patent No. 6,012, 101. Further details of the system are provided below with respect to Figure 2.

#### Figure 2: A Computer Card Including A Slide Drawer Frame

Figure 2 illustrates one embodiment of computing system 108 in the form of a computer card. As Figure 2 shows, in one embodiment the computing system may include slide drawer frame 205, printed circuit board 207 (or motherboard) mounted to the frame 205, and non-volatile memory 208 such as a hard drive or optical drive, also comprised on the frame 205. The computer card may communicate with external systems via edge connector 209. In one embodiment the edge connector 209 may be operable to communicate network signals with a network and an encoded set of human interface signals including video, keyboard, mouse, USB, and other human interface device signals with human interface 113. In one embodiment the computing system may further include power supply 210 mounted on the frame 205 and coupled to an external power source, which may be operable to provide power at the proper voltages to the computer 108.

As Figure 2 also shows, in one embodiment the computer card 108 may be included in a system of co-located computers. The system may include a cabinet, referred to as a cage 211, having a plurality of slots 212. The computer card may be adapted to be inserted into one of the slots of the cage. The cage 211 may include a cage connector which is adapted to couple to the edge connector 209 on the computer card. The cage connector may also include an external second connector which is electrically coupled to the computer card 108 when the computer card 108 is inserted into the slot. The external second connector may be further adapted to couple to the one or more cables 105 for communication of the encoded one or more human interface signals with the remote location, i.e., the remote human interface 113. The use of the cage connector as an intermediate connection between computer cards 108 and the cables 105 allows the removal and/or exchange of computer cards 108 without the need to disconnect the cables 105 from the cage. If a particular computer card unit becomes non-functional, it may be removed and a new computer card inserted in its place very simply and quickly. In addition, the coupling of the computer cards 108 to the human interface through the cage connector may allow the easy insertion of removable function modules, described below with reference to Figures 6-9.

In the preferred embodiment of the invention, the computer card 108 is operable to slide into a slot of the cage 211, thereby making contact with the cage connector. The computer card may comprise a complete PC on a single slide drawer frame which may be only 3 rack units high (5.25 inches), and thus may occupy a much smaller space than standard PC units. Further details of the computer card 108 are presented below with reference to Figure 3.

### 25 Figure 3: A Computer On A Card

Figure 3 illustrates the computer card of Figure 2, according to one embodiment. As Figure 3 shows, the computer 108 may include a subset or all of the elements that make up a standard Personal Computer, such as PC motherboard 207 with various components such as a microprocessor CPU 306, memory 304, and interface logic 303

configured on a single card. In one embodiment, the interface logic 303 may include I/O logic 307, network logic 305, and human interface logic 303. In one embodiment, the network logic 305 may include a LAN interface, Ethernet, or any other network interface. In one embodiment, the I/O logic 307 may include video, audio, USB, and/or any other I/O interface circuitry associated with a PC motherboard. As shown, the computer card 108 may also include interfacing edge connector 209, which may be operable to transmit video, mouse, keyboard, USB, and Ethernet signals, as well as any other peripheral or network signals. In one embodiment, the edge connector 209 may include a human interface connector which may be operable to communicate human interface signals between the human interface logic 303 and human interface 113.

The human interface logic 303 comprised on the printed circuit board 207 may be operable to receive one or more human interface signals 107 from the I/O logic and encode the signals into a format suitable for transmission to a remote location, i.e., the remote human interface 113. In one embodiment the human interface logic 303 may be adapted to couple to the one or more cables 105 for transmission of the encoded human interface signals 107 to the remote location, such as through the human interface connector comprised on edge connector 209. In one embodiment, the human interface logic 303 may also be operable to receive one or more incoming encoded human interface signals 107 from the remote human interface 113 through the human interface connector, and to decode the incoming encoded human interface signals 107 to produce decoded human interface signals which may be transmitted to the I/O logic for use in the computing system. In one embodiment the human interface signals 107 sent and received by the human interface logic 303 may be encoded into a format for transmission over a distance exceeding 20 feet. In another embodiment, the human interface logic 303 may be operable to send and receive two or more encoded human interface signals 107 to and from the remote location. In yet another embodiment, the human interface logic 303 may be operable to send and receive three or more encoded human interface signals 107 to and from the remote location. For more information regarding the encoding and transmission of human interface signals over extended distances, please see U.S. Patent No. 6,038,616

titled "Computer System With Remotely Located Interface Where Signals Are Encoded At The Computer System, Transferred Through A 4-Wire Cable, And Decoded At The Interface" by Thornton, et al., which is incorporated by reference above.

5 In one embodiment, the human interface signals 107 communicated between the computer 108 and the human interface 113 may include one or more of a video signal, keyboard signal, and pointing device signal, such as a mouse signal. In another embodiment, the communicated human interface signals 107 may include two or more of a video signal, keyboard signal, and pointing device signal. In a further embodiment, the communicated human interface signals 107 may include three or more of a video signal, keyboard signal, pointing device signal, and audio signal. In yet another embodiment, the human interface signals 107 may include USB signals for communication with one or more USB devices.

15 In one embodiment, interface logic of the computing system 108 may include keyboard logic comprised on the printed circuit board 207 for interfacing to keyboard 110. The keyboard logic may be coupled to the human interface logic and may be operable to generate keyboard signals that are provided to the human interface logic as part of the communicated human interface signals described above. The human interface logic 303 may also be operable to receive encoded keyboard signals as part of the encoded human interface signals described above, and to decode the encoded keyboard signals. The keyboard logic may be further operable to receive the decoded keyboard signals from the human interface logic 303.

25 In one embodiment, interface logic of the computing system 108 may include pointing device logic comprised on the printed circuit board 207 for interfacing to a pointing device 111. The pointing device logic may be coupled to the human interface logic 303 and may be operable to generate pointing device signals that are provided to the human interface logic 303 as part of the communicated human interface signals described above. The human interface logic 303 may also be operable to receive encoded pointing device signals as part of the encoded human interface signals 107 described above, and to decode the encoded pointing device signals. The pointing device logic may be further



operable to receive the decoded pointing device signals from the human interface logic 303.

In one embodiment, interface logic of the computing system 108 may include USB logic comprised on the printed circuit board 207 for interfacing to a USB device.

5 The USB logic may be coupled to the human interface logic 303 and may be operable to generate USB signals that are provided to the human interface logic 303 as part of the communicated human interface signals described above. The human interface logic 303 may also be operable to receive encoded USB signals as part of the encoded human interface signals described above, and to decode the encoded USB signals. The USB  
10 logic may be further operable to receive the decoded USB signals from the human interface logic 303.

In one embodiment, interface logic of the computing system 108 may include video logic comprised on the printed circuit board 207 for interfacing to a video device.

The video logic may be coupled to the human interface logic 303 and may be operable to  
15 generate video signals that are provided to the human interface logic 303 as part of the communicated human interface signals described above. The human interface logic 303 may also be operable to receive encoded video signals as part of the encoded human interface signals 107 described above, and to decode the encoded video signals. The video logic may be further operable to receive the decoded video signals from the human  
20 interface logic 303.

In one embodiment, interface logic of the computing system 108 may include audio logic comprised on the printed circuit board 207 for interfacing to an audio device.

The audio logic may be coupled to the human interface logic 303 and may be operable to generate audio signals that are provided to the human interface logic 303 as part of the  
25 communicated human interface signals described above. The human interface logic 303 may also be operable to receive encoded audio signals as part of the encoded human interface signals 107 described above, and to decode the encoded audio signals. The audio logic may be further operable to receive the decoded audio signals from the human interface logic 303.

In one embodiment, the computing system may further comprise network interface logic 305 comprised on the printed circuit board for interfacing to a network. The network logic 305 may be operable to encode network signals into a format suitable for transmission to the network. The network logic 305 may also be operable to receive  
5 encoded network signals from the network, and to decode the encoded network signals.

In one embodiment, the motherboard 207 may further include logic supporting PCI slot-based feature cards. The computer card 108 may also include one or more hard disk drives 208 or optical drives, and a power supply 210 which may be operable to convert the local main power to the appropriate voltages for the computer 108.

10 In a preferred embodiment, the computer card may have a long rectangular form factor, with the computer components mounted on one side. The computer card may be electrically coupled to the cage through edge connector 209 which faces to the rear of the computer card assembly. In the preferred embodiment the order of the elements from front to back are set to provide the greatest cooling for the hottest elements. The interface  
15 logic 302, which may comprise network logic 305, such as one or more LAN or WAN connections, typically IEEE803.2 (10/100 BaseT) Ethernet, as well as I/O logic 307 and human interface logic 303 for connecting to the human interface devices (HID), is located at the rear of the computer card frame, while the power supply and non-volatile memory (disk drive) are located at the front of the frame. The fact that each computer card has its  
20 own power supply on-board means that in the event of a power supply failure, only the affected computer card will fail. This feature is in contrast with prior art systems in which there is a single power supply located in the cabinet which supplies power to multiple computing units, thus presenting a single point of failure for the system.

In various other embodiments, the computer card may have various different form  
25 factors, including two dimensional forms, such as a square or rectangles of various proportions, as well as three-dimensional forms, such as a cubic form, or three dimensional rectangular forms of various proportions. In various embodiments, the computer card may be designed with components mounted on either or both sides of the

card. In the various three dimensional embodiments, the components may be mounted on the inside surfaces of the form, the outside surfaces of the form, or both.

#### Figure 4: Multiple Computer Systems With Human Interfaces

5           Figure 4 illustrates an embodiment of the system in which multiple computer cards 108 are inserted into the slots of the cage 211. As Figure 4 shows, each computer card 108 may be coupled to a plurality of human interface devices through the cage connector and cables. As shown, computer card 108A may be inserted into cage slot 212A, and may thereby be coupled to keyboard 110A, mouse, 111A, and monitor 112A, which comprise the human interface 113A for that computer card. Computer cards 108B and 108C may be similarly inserted into respective slots 212B and 212C and coupled to respective human interface devices 113B and 113C as shown. Thus, the computer cards 108 may all be installed in the cage 211 at a central location, while the user interface 113 for each computer card 108 may be located remotely from the cage, such as at the  
10           respective work areas of the users of the computer cards. It should be noted that the human interface devices shown here are for illustration purposes only, and that the actual type and number of devices comprised in each human interface may vary.

          Figure 4 also shows that each computer card 108 may be coupled to a network 404. As described above with reference to Figure 3, each computer card may include  
20           network logic for interfacing to the network 404. The network 404 may be one or more of a Local Area Network (LAN) or a Wide Area Network (WAN), such as the Internet.

          The use of the cage assembly 211 to couple the computer cards 108 to their respective human interfaces 113 provides modularity to the system which may be used to deploy removable function modules, described below with reference to Figures 6-9.

25

#### Figure 5: A Block Diagram Of Multiple Computer Systems With Remote Human Interfaces

          Figure 5 is a block diagram of the system described above with reference to Figure 4. As Figure 5 shows, the cage 211 may include cage connector 509 which is

operable to couple to one or more human interface cables 105 for coupling to human interface devices and to one or more network cables 511 for coupling to one or more networks, respectively. In one embodiment, the computer cards 108 may be inserted into respective slots 212 of the cage 211, and coupled to respective user interfaces 113 through cage connector 509 and one or more human interface cables 105, such as cable 105A. Each user interface 113 may include one or more human interface devices, such as keyboard 110, mouse, 111, and monitor 112, or any other human interface device. As Figure 5 also shows, each computer card 108 may also be coupled to network 404 through the cage connector 509 and the one or more network cables 511, such as 511A. In one embodiment, the network cable 511 may comprise an Ethernet cable. Thus, multiple computer cards 108 may be installed in a centrally located computer cage 211, and coupled to remote human interfaces 113 and network 404.

#### Figure 6: Computer System With Removable Function Modules

Figure 6 illustrates one embodiment of the computer system of Figures 4 and 5 with a removable function module. As Figure 6 shows, the computer card 108 may be operable to slide into the computer cage 211, thereby engaging the computer card edge connector 209 with the cage connector 509. A removable function module 602 may be operable to engage the cage connector 509 via a module connector 609 which comprises a circuit board edge connector. As shown, the cage connector 509 may include a vertical connector which accepts the computer card edge connector 209, and a second, horizontal, connector which accepts the horizontal module connector 609. The cage connector 509 is therefore operable to turn the vertical signal path from the computer card 108 ninety degrees and connect to the horizontal module connector 609 of the function module 602. The use of the cage connector 509 as an intermediate connection between the computer cards 108 and the function module 602 allows the removal and/or exchange of computer cards 108 without the need to disconnect the cables from the cage, as well as the removal and/or exchange of the function module 602 without the need to disconnect the computer cards 108.

In one embodiment, the function module 602 may include interfacing cable connectors 610 corresponding to each computer card slot 212 in the cage 211. The cable connectors 610 may be operable to couple to one or more cables for communicating with external systems, such as networks and/or human interface devices. In one embodiment, the external connectors used for the cable connectors may be standard connectors, including one or more of RJ45, db9, db25, or dbhd15 connectors, or any other type of standard connector.

#### Figure 7: Removable Function Module

Figure 7 illustrates one embodiment of a removable function module in greater detail. As Figure 7 shows, the function module 602 may include module connector 609 which is operable to connect to the cage 211 via cage connector 509, thereby coupling to the computer cards 108 which are inserted into respective slots 212 of the cage 211. The function module 602 may further include one or more network cable ports 706 for receiving one or more network cables 511 to interface with one or more networks 404, as well as one or more human interface cable ports 708 for receiving one or more human interface cables 510 to interface with one or more human interfaces 113. In one embodiment, the cable ports may comprise RJ-45 connectors. In addition, the function module 602 may also include a power supply 704 which may be operable to supply power to the function module components. Further embodiments of the function module 602 are described below with reference to Figure 8.

#### Figure 8: A Multi-Board Function Module

Figure 8 illustrates one embodiment of a multi-board removable function module. In one embodiment, a function module 602A may include circuitry which provides additional functionality to the computer cards 108. As Figure 8 shows, the function module 602A may include multiple circuit boards to provide multiple additional functions to the computer system. In one embodiment, the function module 602A may include a top cover 804 and a bottom cover 810 which may encapsulate multiple circuit

boards, such as a network board 808 and a layer 3 switch and router (SW3) board 806. In one embodiment, the network board 808 may comprise an Ethernet board with active Ethernet Switch types 1 and 2. In one embodiment, the SW3 board 806 may comprise an Ethernet Level 3 Switch and Router board. In one embodiment, the Ethernet board 808  
5 may connect to the cage connector 509, while the SW3 board 806 is "piggybacked" on the Ethernet board 808. The Ethernet board 808 may be operable to pass certain signals upward to the piggybacked SW3 board 806, thus permitting additional signal processing to occur.

In one embodiment, a first removable function module 602, such as that described  
10 above with reference to Figure 7, and which may be operable to provide a first functionality, such as interfacing the plurality of computer cards 108 with human interfaces 113 and a network 404, may be removed and replaced with a second removable function module 602A, such as the multi-board module described above, which may be operable to provide a second, additional, functionality. It should be noted that the  
15 function module exchange may be accomplished without the removal of the computer cards 108 from the cage 211. Thus, a variety of removable function modules 602 may be deployed to provide various additional functions to the plurality of computer cards 108 as desired.

In one embodiment, the function module 602 may include at least one cable  
20 connection module which is operable to provide cable connections to one or more cables for the plurality of computer cards 108.

In one embodiment, the function module 602 may include at least one network card, wherein the at least one network card is operable to provide a network interface to the plurality of computer cards 108.

25 In one embodiment, the function module 602 may include at least one network switch which is operable to perform network switching functions for the plurality of computer cards 108.

In one embodiment, the function module 602 may include at least one data switch which is operable to perform data switching functions for the plurality of computer cards 108.

5 In one embodiment, the function module 602 may include at least one router which is operable to perform network routing functions for the plurality of computer cards 108.

In one embodiment, the function module 602 may include at least one network processing unit which is operable to perform network processing functions for the plurality of computer cards 108.

10 In one embodiment, the function module 602 may include a Gigabit Ethernet network interface which includes a Gigabit Ethernet bus, wherein the Gigabit Ethernet network interface comprises a plurality of Gigabit Ethernet ports for each of at least a subset of the plurality of computer cards 108.

15 In one embodiment, the function module 602 may include at least one gateway which is operable to perform gateway functions for the plurality of computer cards 108.

In one embodiment, the function module 602 may include at least one firewall which is operable to restrict network access to the plurality of computer cards 108.

20 In one embodiment, the function module 602 may include a human interface switching unit, wherein the human interface switching unit is configurable to route encoded human interface signals from one or more of the plurality of computer cards to one or more of a plurality of remote human interface devices coupled to the removable function module 602.

25 In one embodiment, the function module 602 may include at least one analog POTS unit which is operable to provide standard analog telephony services to the plurality of computer cards 108.

In one embodiment, the function module 602 may include at least one digital telephone which is operable to provide digital telephony services to the plurality of computer cards 108.

In one embodiment, the function module 602 may include at least one PBX unit which is operable to provide PBX services to the plurality of computer cards 108.

In one embodiment, the function module 602 may include at least one Voice over Internet Protocol (VoIP) telecommunication device which is operable to provide VoIP services to the plurality of computer cards 108.

In one embodiment, the function module 602 may include at least one MPEG video unit which is operable to provide MPEG video services to the plurality of computer cards 108.

10 Figure 9: A Method For Configuring A Plurality Of Computing Systems

Figure 9 is a flowchart of a method for configuring a plurality of computing systems, according to one embodiment. As shown in Figure 9, a plurality of computer cards 108 may be inserted into a cage 211, as indicated in 902. In one embodiment, the inserted computer cards 108 may each make electrical contact with cage connector 509, as described above with reference to Figures 5 and 6.

In 904, a first removable function module 602 may be attached to the cage 211, thereby coupling to at least a subset of the inserted computer cards 108. As described above with reference to Figures 6 and 7, the function module 602 may electrically couple to the inserted computer cards via module connector 609 which connects to the cage connector 509. In one embodiment, attaching the first removable function module 602 to the cage 211 may include attaching one or more cables to the cable connectors 610 to interface with external systems. For example, one or more network cables 511 may be connected to network cable ports 706 for interfacing to one or more networks 404, and one or more human interface cables 510 may be connected to human interface ports 708 for interfacing to one or more human interfaces 113. In one embodiment, one or more cables may be connected to the function module 602 to couple the inserted computer cards to a telephone line. The first removable function module 602 may be operable to provide a first functionality to the inserted computer cards 108, and may include any of the function modules described above with respect to Figure 7.



In 906, the first removable function module 602 may be removed from the cage assembly 211. In one embodiment, removing the first removable function module 602 from the cage 211 may include removing some or all of the one or more attached cables 511 and 510.

5           Finally, in 908, a second removable function module 602 may be attached to the cage 211, thereby coupling to at least a subset of the inserted computer cards 108. As described above with reference to Figures 6 and 7, the function module 602A may electrically couple to the inserted computer cards via module connector 609 which connects to the cage connector 509. In one embodiment, attaching the second removable  
10   function module 602 to the cage 211 may include attaching one or more cables to the cable connectors 610 to interface with external systems. For example, one or more network cables 511 may be connected to network cable ports 706 for interfacing to one or more networks 404, and one or more human interface cables 510 may be connected to human interface ports 708 for interfacing to one or more human interfaces 113. In one  
15   embodiment, one or more cables may be connected to the function module 602 to couple the inserted computer cards to a telephone line. The second removable function module 602 may be operable to provide a second functionality to the inserted computer cards 108, and may include any of the function modules described above with respect to Figure 8.

          Thus, in various embodiments, a variety of removable function cards 602 may be  
20   added and/or removed from the cage assembly to provide various sets of functionality to the inserted computer cards 108 as needed. The fact that both the computer cards 108 and the function modules 602 may be removed from the cage assembly 211 without removing the other greatly simplifies the process of configuring and reconfiguring the system.

25           The system and method described above solve many of the problems of the prior art. By centralizing the location of the computing elements while permitting the remote location of the human interfaces to the computers, the management of both the hardware and software may be greatly simplified. The inclusion of removable function modules in the system provides a simple and affordable mechanism whereby additional feature sets

may be provided for the plurality of computing systems as required. The use of function modules as described above enables an administrator to apply standard feature sets to multiple computing systems with ease and greatly decreases cabling requirements for the system by eliminating installation wiring between the computers and the additional feature set devices (function modules). Additionally, the feature set hardware may be added without requiring any additional vertical installation space. Finally, the various feature set devices may be added to and removed from the system without requiring any other equipment to be moved.

Further modifications and alternative embodiments of various aspects of the invention will be apparent to those skilled in the art in view of this description. Accordingly, this description is to be construed as illustrative only and is for the purpose of teaching those skilled in the art the general manner of carrying out the invention. It is to be understood that the forms of the invention shown and described herein are to be taken as the presently preferred embodiments. Elements and materials may be substituted for those illustrated and described herein, parts and processes may be reversed, and certain features of the invention may be utilized independently, all as would be apparent to one skilled in the art after having the benefit of this description of the invention. Changes may be made in the elements described herein without departing from the spirit and scope of the invention as described in the following claims.